



INSTALLATION GUIDE

CTS Turbo MK7 Golf R/GTI Intake



20630 Mufford Crescent, Unit #309
Langley, British Columbia V2Y 2V9

www.CTSTURBO.com

WHAT IS INCLUDED

1. Silicon Coupler
2. Air Filter
3. Intake Pipe
4. Heatshield & Hardware
5. Heatshield mounting grommets
6. *SAI filter if you have a GTI

TOOLS REQUIRED

1. Flat blade screwdriver
2. 7mm, 8mm, 10mm Sockets
3. 2.5mm Allen




NOTES

Vehicle used in this guide is a MK7 GOLF R/GTI. Always make sure the car is safe to work on. Do not work on a hot motor. We do not accept any liability for incorrect installation or damage during the install.

STEP 1

Loosen the hoseclamp on the rear of the intake pipe using a 7mm socket or flathead screwdriver



STEP 2

Disconnect the small vacuum line from the side of the airbox




STEP 3

Disconnect the rear intake pipe



STEP 4

Remove the airbox by pulling up on the drivers corner, then straight up.



STEP 5


Remove the stock intake



If you have a Golf R continue to Step 7


STEP 6

Connect and install the secondary air injection (SAI) and CTS SAI filter with provided zip tie



STEP 7


Install the supplied bolt here,
only thread it half-way



STEP 8

Install the rear silicon coupler
with the supplied clamps.

Tighten the lower clamp



STEP 9

Install the new CTS heatshield, we recommend you lube the grommets with a small amount of WD-40 to make installation easier.



STEP 10

When installing the CTS intake pipe, re-connect the vacuum line we disconnected in 'Step 2'



STEP 11

Install the CTS intake pipe into the rear Silicone coupler, tighten all your clamps & the 10mm bolt that was pre-installed in "step 7"



STEP 12

You are done!

